

GTD368-6SR : 4"(10.2cm), - 6-digit - red/ Green /Blue/ Yellow LEDs



Features:

- 4"(10.2cm), - 6-digit - hh:mm:ss
- Available in double-sided—only a display screen is needed
- Time is automatically set by Simple Network Time Protocol (SNTP)
- DHCP or Static IP addressable
- Power over Ethernet (IEEE802.3af POE) or – 12VDC Power
- All international time zones
- Daylight saving time selectable
- Receive time from Network or Time sever- No master clocks required
- Installation options: Surface, Pendant, Cantilever
- Brightness available in 4 levels
- 12/24 hour format display-hh:mm:ss
- CE / FCC Marked

Specification:

- Display: 6-digit, 7-segment LEDs
- Viewing Distance: 150 feet
- Cabinets: black plastic or painted steel
- Accuracy: +/- approximately 20 milliseconds
- Operating Temperature: -10°C to 60°C
- Operating Humidity: 90% maximum, non-condensing
- Power Consumption: less than 9W
- Power Supply: POE or 12VDC
- Time Synchronization: SNTP/NTP



WINspect Technologies Pvt. Ltd

502, Bldg No. 6 ,Balaji Garden, Plot No. 17,Sector-11 Koparkhairane , Navi Mumbai-400709.
Email- info@winspectindia.com Fax.: 022-27547518 ; Tel.:9820267947