

DUC-1

DOWN/UP CONVERTER (COAXIAL)



Our StarLink™ GPS Down/Up converter makes it possible for long cable runs up to 450 meters.

The DUC converters are the perfect add-on for L1 GPS installations where long antenna cables are needed and a simple in-line amplifier will not suffice.

A DUC consists of a combined GPS antenna and down-converter and an up-converter at the RF input of the GPS receiver.



The technology phase locks the converter pair to provide high fidelity signal transport.

This technique uses the same reference for up and down conversion, eliminating frequency error.

The DUC product is optimized for generic RG-58 cable and can be used for lengths of up to 450 meters.

Specifications:

- GPS Frequency: L1 (1575.42 MHz)
- Cable Distance to Antenna: 457.2m (1500 ft)
- Cable Distance to Receiver: 30m (100 ft)
- Coax Cable Type: 50 Ohm

DUC-1 SPECIFICATIONS



DOWN CONVERTER

APPLICATIONS

- Low emissions.
- Replaces long cable runs & high gain antennas.
- · Easy installation, since cable length is not critical.
- Decreased susceptibility to lightning strike damage

SPECIFICATIONS

• Frequency: GPS L1

Gain Combined: 35 (min)

Axial Rate: 3 dB (max)

Noise Figure:
 2.5 dB (max)

• Termination: 50 0

SIZE AND WEIGHT

• Height: 89 mm (3.5")

• Diameter: 114 mm (4.5")

• Weight: < .45 kg (1.0 lbs)

ENVIRONMENTAL

Relative Humidity: 0-100% condensing

• Storage Temperature: -55°C to +85°C

• Operating Temperature: -40°C to +65°C

• Altitude: 6,096 m (20,000 ft)

OTHER

• Connection: TNC, Female

Packaging: Waterproof (IP67) enclosure

Mounting: Standard marine mount,

1" - 14 or 3/4" NPT

UP CONVERTER

SIZE AND WEIGHT

• Dimensions: 44 x 130 x 170 mm

(1.75 x 5.12 x 6.68 in)

• Weight: 0.6 kg (1.3 lbs)

POWER

• Power Requirements: 9-12 VDC via antenna bias2

or 12 ±10% VDC external

• Power Consumption: < 250 mA @ 12 VDC

(Both Units)

ENVIRONMENTAL

Relative Humidity:
 0-95% non-condensing

• Storage Temperature: -50°C to +85°C

• Operating Temperature: 0°C to +50°C

Altitude: 6,096 m (20,000 ft)

OTHER

Connection: BNC connector to down converter,

TNC to GPS receiver.

• Indications: Power

Fault for Down converter

Cable open or short

ANTENNA CABLE LENGTHS (Max.)

• Copper DUC 450 m (1,500 ft)*

*RG-58 cable

US patent 5,999,795

Førsberg

www.forsbergservices.co.uk
TEL: +44(0)1524-383320 | EMAIL: info@forsbergservices.co.uk